

Blue Star 5100



Product Description:

Type:

A high-quality, matte, plastic (emulsion) paint, specifically designed for use as a primer/undercoat. Its acrylic base ensures strong adhesion to most interior surfaces. It features exceptional coverage and leveling, providing a uniform preparatory layer that minimizes the consumption of the final topcoat. It is easy to mix and apply and dries quickly to speed up painting operations .

Usage:

It is used to prepare exterior surfaces, both new and old, such as brick, concrete, cementitious surfaces, and gypsum boards.

Key Features:

1. Excellent adhesion to interior surfaces.
2. High opacity and excellent coverage.
3. Smooth and uniform matt finish.
4. Good leveling properties.
5. Reduces topcoat consumption.
6. Easy to apply.
7. Suitable for use as a primer and undercoat.

Application Method:

Ensure that the surface is clean, dry, and free from dust, grease, and loose particles. Repair cracks and imperfections and apply one coat of acrylic sealer if required. Stir the paint thoroughly before use and dilute with clean water by 5–10% for brush or roller application and 10–15% for airless spray application. Apply two uniform coats, allowing 2–3 hours between coats.

Blue Star 5100



Product Properties:

Appearance	Matt
Color	White
Viscosity	115 ± 5KU
Solid Content	60 ± 2
Coverage Rate	4 - 5 m ² per 1 kg
Thinning	7-10 % using clean water.
Surface Drying	30 – 45 Minutes
Recoat Time	2 – 3 Hours
Full Cure	24 Hours

Blue Star 5100



Application Tools:

Air compressor.



Paint Roller.



Paintbrush.



Packaging:

18 Kg

Storage and Shelf Life:

- 1- Store the product in its original, tightly closed container in a well-ventilated area away from direct sunlight and heat.
- 2- The product remains valid for 12 months from the date of production.

Safety and Precautions:

- 1- Do not store food inside the empty container.
- 2- Avoid contact with eyes. In case of contact, rinse immediately with water and seek medical advice.

Warranty:

We guarantee the quality of our products as stated in this data sheet, which reflects our extensive experience and the tests conducted on the product..