

PRIMER 134



Product Description:

Type:

A high-quality clear water-based acrylic sealer designed to penetrate and stabilize porous surfaces while improving the adhesion of subsequent paint and putty coats. It reduces surface absorbency, enhances paint coverage, and improves the durability of the coating system.

Usage:

Used as a penetrating primer on concrete, cement plaster, gypsum putty, brickwork, blockwork, and other porous mineral surfaces. Suitable for interior and exterior applications to reduce surface absorbency, improve adhesion, and prepare substrates before the application of putty, primer, or decorative paints.

Key Features:

1. Deep penetration into porous substrates.
2. Improves adhesion of subsequent coatings.
3. Reduces surface absorbency.
4. Enhances paint coverage and performance
5. Good resistance to moisture and alkalinity.
6. Dries transparent.
7. Easy to apply.

Application Method:

Ensure the surface is clean, dry, sound, and free from dust, grease, and loose particles. Apply the sealer evenly by brush, roller, or spray. Allow to dry completely before applying putty, primer, or paint.

PRIMER 134



Product Properties:

Appearance	Milky White Liquid (Transparent When Dry)
Binder Type	Pure Acrylic Emulsion
Density	1.00 ± 0.05 g/cm ³
Viscosity	65 – 80 KU
Solid Content	15 – 20 %
Surface Dry Time	60– 90 Minutes
Recoating Time	2 – 4 Hours
Full Cure	24 Hours
Coverage Rate	8 – 12 m ² /L/Coat
Thinning	10 – 15% Clean water

PRIMER 134



Application Tools:

Air compressor. Paint Roller. Paintbrush.



Packaging:

10 Kg

Storage and Shelf Life:

- 1- Store the product in its original, tightly closed container in a well-ventilated area away from direct sunlight and heat.
- 2- The product remains valid for 12 months from the date of production.

Safety and Precautions:

- 1- Do not store food inside the empty container.
- 2- Avoid contact with eyes. In case of contact, rinse immediately with water and seek medical advice.

Warranty:

We guarantee the quality of our products as stated in this data sheet, which reflects our extensive experience and the tests conducted on the product..