

## Primer 200 Insulator



### Product Description:

#### Type:

A high-quality, white, water-based sealer designed to protect exterior facades and walls. It works by sealing surface pores and forming a protective barrier that is waterproof and weather-resistant, while preserving the original appearance of the surface.

#### Usage:

It is used to prepare exterior surfaces, both new and old, such as brick, concrete, cementitious surfaces, and gypsum boards.

#### Application:

- 1- The surfaces to be painted must be level, clean, free of dust, grease, oils, and completely dry.
2. Apply one coat of Primer 200 to seal the pores in the wall.
3. Old painted surfaces should be cleaned first from all loose paint and other contaminants that can affect adhesion.

### Product Properties:

Color	White
Appearance	Matt
Viscosity	115 + 5KU
Solid Content	60 ± 2
Coverage Rate	6 - 7 m <sup>2</sup> per 1 kg
Thinning	10-15 % with water
Surface Drying	1 hour
Full Drying	2-4 hours

## Primer 200 Insulator



### Application Tools:

Air compressor.



Paint Roller.



Paintbrush.



### Packaging:

4 Kg ,12 Kg

### Storage and Shelf Life:

- 1- Store the product in its original, tightly closed container in a well-ventilated area away from direct sunlight and heat.
- 2- The product remains valid for 12 months from the date of production.

### Safety and Precautions:

- 1- Do not store food inside the empty container.
- 2- Avoid contact with eyes. In case of contact, rinse immediately with water and seek medical advice.

### Warranty:

We guarantee the quality of our products as stated in this data sheet, which reflects our extensive experience and the tests conducted on the product..