

Elmadina Putty 500



Product Description:

Type:

A ready-to-use interior wall putty formulated with high-quality acrylic copolymer binders and selected mineral fillers. It provides excellent filling properties, smooth application, and superior workability, allowing multiple coat applications to create a uniform and durable surface ready for painting. It also offers good adhesion and easy sanding for a high-quality decorative finish.

Usage:

Used for preparing new or old interior surfaces such as brick, concrete, cement surfaces, and gypsum boards.

Application:

1. The surface to be painted must be smooth, clean, free from dust, grease, and oils, and completely dry.
2. Apply one coat of Primer 100 to seal the pores in the wall.
3. Apply two or three coats of Elmadina Putty 500 one in a longitudinal direction and the other in a cross direction.
4. After drying, sand the surface and remove dust completely.

Product Properties:

Color	White
Appearance	Matt / Flat
Viscosity	Gel-like putty
Solid Content	65% ± 2
Coverage Rate	2–3 m ² /kg depending on surface condition
Surface Drying	1 hour
Full Drying	12 hours

Elmadina Putty 500



Application Tools:



Putty Knife.

Packaging:

1 Kg, 4 Kg, 18 Kg, 25 Kg

Storage and Shelf Life:

- 1- Store the product in its original, tightly closed container in a well-ventilated area away from direct sunlight and heat.
- 2- The product remains valid for 12 months from the date of production.

Safety and Precautions:

- 1- Do not store food inside the empty container.
- 2- Avoid contact with eyes. In case of contact, rinse immediately with water and seek medical advice.

Warranty:

We guarantee the quality of our products as stated in this data sheet, which reflects our extensive experience and the tests conducted on the product..