

STUCCO 999



Product Description:

Type:

High-performance polymer-modified cementitious wall putty designed for repairing, leveling, and smoothing interior and exterior walls. It provides excellent adhesion, high durability, crack resistance, and a smooth finish suitable for painting.

Usage:

Suitable for concrete surfaces, cement plaster, blockwork, brick walls, and exterior facades. Ideal for preparing surfaces before the application of decorative paints and protective coatings.

Key Features:

1. Excellent adhesion to cementitious substrates.
2. High resistance to cracking and shrinkage.
3. Water-resistant and weather-resistant.
4. Smooth and uniform finish.
5. Easy mixing and application.
6. Suitable for interior and exterior use.
7. Good breathability and durability.

Application Method:

Mix the product with clean water using a mechanical mixer until a smooth, lump-free consistency is achieved. Allow the mixture to stand for 3–5 minutes and remix before use. Apply with a steel trowel in thin layers over a clean, sound, and slightly damp substrate. After drying, lightly sand if required and proceed with painting after complete curing.

STUCCO 999



Product Properties:

Appearance	Grey or White Powder
Base Material	Cement, Mineral Fillers & Polymers
Density	1.50 ± 0.10 g/cm ³
Mixing Ratio	28 – 32% Water by Weight
Pot Life	1 – 2 Hours
Initial Setting Time	2 – 4 Hours
Final Setting Time	8 – 12 Hours
Application Thickness	1 – 3 mm per coat
Drying Time Between Coats	4 – 6 Hours
Painting Time	24 – 48 Hours

STUCCO 999



Application Tools:



Putty Knife.

Packaging:

20 Kg

Storage and Shelf Life:

- 1- Store the product in its original, tightly closed container in a well-ventilated area away from direct sunlight and heat.
- 2- The product remains valid for 12 months from the date of production.

Safety and Precautions:

- 1- Do not store food inside the empty container.
- 2- Avoid contact with eyes. In case of contact, rinse immediately with water and seek medical advice.

Warranty:

We guarantee the quality of our products as stated in this data sheet, which reflects our extensive experience and the tests conducted on the product..